

Tutorial: Programming in Java for Android Development

Adam C. Champion and Dong Xuan

CSE 4471: Information Security

Autumn 2013


Based on material from C. Horstmann [1], J. Bloch [2], C. Collins et al. [4],
M.L. Sichitiu (NCSU), V. Janjic (Imperial College London), CSE 2221 (OSU), and other sources

Outline



- **Getting Started**
- Java: The Basics
- Java: Object–Oriented Programming
- Android Programming

Getting Started (1)

- Need to install Java Development Kit (JDK) to write Java (and Android) programs
 - **Do not** install Java Runtime Environment (JRE); JDK and JRE are different!
- Can download the JDK for your OS at <http://java.oracle.com>
- Alternatively, for OS X, Linux:
 - OS X:
 - Open /Applications/Utilities/Terminal.app
 - Type `javac` at command line
 - Install Java when prompt appears
 - Linux:
 - Type `sudo apt-get install default-jdk` at command line (Debian, Ubuntu)
 - Other distributions: consult distribution's documentation






Install!



Getting Started (2)


- After installing JDK, download Android SDK from <http://developer.android.com>
- Simplest: download and install Android Developer Tools (ADT) bundle (including Android SDK) for your OS
- Alternatives:
 - Download/install Android Studio (beta) from this site (based on IntelliJ IDEA)
 - Install Android SDK tools by themselves, then install ADT for Eclipse separately (from this site)
- We'll use ADT with SDK (easiest)



Install!


Getting Started (3)

- Unzip ADT package to directory <adt-bundle-os>, then run <adt-bundle-os>/eclipse/Eclipse app. You should see this:




Getting Started (4)

- Go to Eclipse preferences (*Window*→*Preferences* or *ADT*→*Preferences*), select Android tab
- Make sure the Android SDK path is correct (<adt-bundle-os>/sdk)
- Strongly recommend testing with real Android device
 - Android emulator: *very* slow
 - Install USB drivers for your Android device



Getting Started (5)

- Bring up the Android SDK Manager
 - Recommended: Install Android 2.2, 2.3.3 APIs and 4.x API
 - Do not worry about Intel x86 Atom, MIPS system images




- In Eclipse, click *Window*→*Show View*→*Other...* and select views *Android*→*Devices*, *Android*→*LogCat*
- Now you're ready for Android development!

Outline

- Getting Started
- **Java: The Basics**
- Java: Object–Oriented Programming
- Android Programming

Java Programming Language

- Java: general-purpose language designed so developers write code once, it runs anywhere
- The key: Java Virtual Machine (JVM)
 - Program code compiled to JVM bytecode
 - JVM bytecode interpreted on JVM
- We'll focus on Java 5 (Android uses this). See chapters 1–7 in [1].




Our First Java Program (1)


```
public class HelloWorld
{
    public static void main(String[] args)
    {
        System.out.println("Hello world!");
    }
}
```

- Don't forget to match curly braces {,} or semicolon at the end!
- In Eclipse: *File*→*New*→*Java Project*, name project "HelloWorld" (no quotes), click Finish. Open HelloWorld in Package Explorer. Right-click src directory, select *New*→*Class*, and create a class HelloWorld with a main() method. To run the program, right-click HelloWorld project, click Run As

Our First Java Program (2)



Right-click,
New→*Class*



Explaining the Program

- Every .java source file contains one class
 - We create a class HelloWorld that greets user
 - The class HelloWorld must have the same name as the source file HelloWorld.java
 - Our class has public scope, so other classes can “see” it
 - We’ll talk more about classes and objects later
- Every Java program has a *method* main() that executes the program
 - Method “signature” must be exactly
`public static void main(String[] args) { ... }`
 - This means: (1) main() is “visible” to other methods; (2) there is “only one” main() method in the class; and (3) main() has one argument (args, an array of String variables)
 - Java “thinks” main(), Main(), miAN() are different methods
- Every Java method has curly braces {,} surrounding its code
- Every statement in Java ends with a semicolon, e.g.,
`System.out.println(“Hello world!”);`
- Program prints “Hello world!” to the console, then quits

Basic Data Types (1)

- Java variables are instances of mathematical “types”
 - Variables can store (almost) any value their type can have
 - Example: the value of a boolean variable can be either `true` or `false` because any (mathematical) boolean value is *true* or *false*
 - Caveats for integer, floating–point variables: their values are subsets of values of mathematical integers, real numbers. Cannot assign *mathematical* 2^{500} to integer variable (limited range) or *mathematical* $\sqrt{2}$ to a floating–point variable (limited precision; irrational number).
 - Variable names must start with lowercase letter, contain only letters, numbers, `_`
- Variable *declaration*: `boolean b = true;`
- Later in the program, we might *assign* `false` to `b`: `b = false;`
- Java strongly suggests that variables be initialized at the time of declaration, e.g., `boolean b;` gives a compiler warning (null pointer)
- Constants defined using `final` keyword, e.g.,
`final boolean falseBool = FALSE;`

Basic Data Types (2)

- Java's primitive data types: [5]

Primitive type	Size	Minimum	Maximum	Wrapper type
boolean	1-bit	N/A	N/A	Boolean
char	16-bit	Unicode 0	Unicode $2^{16} - 1$	Character
byte	8-bit	-128	+127	Byte
short	16-bit	-2^{15}	$+2^{15} - 1$	Short
int	32-bit	-2^{31}	$+2^{31} - 1$	Integer
long	64-bit	-2^{63}	$+2^{63} - 1$	Long
float	32-bit	IEEE 754	IEEE 754	Float
double	64-bit	IEEE 754	IEEE 754	Double

Note: All these types are signed, except char.

Basic Data Types (3)

- Sometimes variables need to be *cast* to another type, e.g., if finding average of integers:

```
int intOne = 1, intTwo = 2, intThree = 3, numInts = 2;  
double doubOne = (double)intOne, doubTwo = (double)myIntTwo, doubThree =  
(double)intThree;  
double avg = (doubOne + doubTwo + doubThree)/(double)numInts;
```
- Math library has math operations like `sqrt()`, `pow()`, etc.
- `String`: immutable type for sequence of characters
 - Every Java variable can be converted to `String` via `toString()`
 - The `+` operation concatenates `Strings` with other variables
 - Let `str` be a `String`. We can find `str`'s length (`str.length()`), substrings of `str` (`str.substring()`), and so on [6]

Basic Data Types (4)

- A literal is a “fixed” value of a variable type
 - TRUE, FALSE are boolean literals
 - ‘A’, ‘\t’, ‘\”’, and ‘\u03c0’ are char literals (escaped tab, quote characters, Unicode value for \pi)
 - -1, 0, 035, 0x1a are int literals (last two are octal and hexadecimal)
 - 0.5, 1.0, 1E6, 6.023E23 are double literals
 - “At OSU”, “Hello world!” are String literals
- Comments:
 - Single-line: // some comment to end of line
 - Multi-line: /* comments span multiple lines */

Common Operators in Java

String	boolean	char	int	double
	!		++ --	
+			+ -	+ -
	&&		* / %	* /
		< >	< >	< >
		<= >=	<= >=	
		== !=	== !=	

Notes:

- Compare String objects using the equals() method, not == or !=
- && and || use *short-circuit evaluation*. To see this, say boolean canPigsFly = FALSE and we evaluate (canPigsFly && <some Boolean expression>). Since canPigsFly is FALSE, the second part of the expression won't be evaluated.
- The second operand of % (integer modulus) must be positive.
- Don't compare doubles for equality. Instead, define a constant like so:
final double EPSILON = 1E-6; // or some other threshold
... // check if Math.abs(double1 - double2) < EPSILON

Control Structures: Decision (1)

- Programs don't always follow “straight line” execution; they “branch” based on certain conditions
- Java decision idioms: if-then-else, switch
- if-then-else idiom:

```
if (<some Boolean expression>)  
{  
    // take some action  
}  
else if (<some other Boolean expression>)  
{  
    // take some other action  
}  
else  
{  
    // do something else  
}
```

Control Structures: Decision (2)

- Example:

```
final double OLD_DROID = 2.0, final double NEW_DROID = 4.0;
double myDroid = 4.1;
if (myDroid < OLD_DROID)
{
    System.out.println("Antique!");
}
else if (myDroid > NEW_DROID)
{
    System.out.println("Very modern!");
}
else
{
    System.out.println("Your device: barely supported.");
}
```

- Code prints "Very modern!" to the screen.
- What if myDroid == 1.1? myDroid == 2.3?

Control Structures: Decision (3)

- Example two:

```
final double JELLY_BEAN = 4.1, final double ICE_CREAM = 4.0;
final double EPSILON = 1E-6;
double myDroid = 4.1;
if (myDroid > ICE_CREAM)
{
    if (Math.abs(myDroid - ICE_CREAM) < EPSILON)
    {
        System.out.println("Ice Cream Sandwich");
    }
    else
    {
        System.out.println("Jelly Bean");
    }
}
else
{
    System.out.println("Old version");
}
```

- Code prints "Jelly Bean" to screen. Note nested if-then-else, EPSILON usage.

Control Structures: Decision (4)

- Other idiom: switch
- Only works when comparing an int or boolean variable against a fixed set of alternatives
- Example:

```
int api = 10;
switch (api)
{
    case 3:  System.out.println("Cupcake"); break;
    case 4:  System.out.println("Donut"); break;
    case 7:  System.out.println("Éclair"); break;
    case 8:  System.out.println("Froyo"); break;
    case 10: System.out.println("Gingerbread"); break;
    case 11: System.out.println("Honeycomb"); break;
    case 15: System.out.println("Ice Cream Sandwich"); break;
    case 16: System.out.println("Jelly Bean"); break;
    default: System.out.println("Other"); break;
}
```

Control Structures: Iteration (1)

- Often, blocks of code should loop while a condition holds (or fixed # of times)
- Java iteration idioms: while, do-while, for
- While loop: execute loop as long as condition is true (checked each iteration)
- Example:

```
String str = "aaaaa";  
int minLength = 10;  
  
while (str.length() < minLength)  
{  
    str = str + "a";  
}  
  
System.out.println(str);
```

- Loop executes 5 times; code terminates when `str = "aaaaaaaaaaa"`
- Notice: if the length of `str` was `minLength`, the while loop would not execute

Control Structures: Iteration (2)

While Loop

```
String str = "aaaaaaaaaa";  
int minLength = 10;
```

```
while (str.length() <  
minLength)  
{  
    str = str + "a";  
}
```

```
System.out.println(str);
```

Do-While Loop

```
String str = "aaaaaaaaaa";  
int minLength = 10;
```

```
do  
{  
    str = str + "a";  
}  
while (str.length() <  
minLength)
```

```
System.out.println(str);
```

Unlike the while loop, the do-while loop executes at least once so long as condition is true. The while loop prints "aaaaaaaaaa" whereas the do-while loop prints "aaaaaaaaaaa" (11 as)

Control Structures: Iteration (3)

- The for loop has the following structure:

```
for (<expression1>; <expression2>; <expression3>)
{
    . . .
}
```

- Semantics:
 - <expression1> is loop initialization (run once)
 - <expression2> is loop execution condition (checked every iteration)
 - <expression3> is loop update (run every iteration)
- Example:

```
int i;
for (i = 0; i < 10; i++)
{
    System.out.println("i = " + i);
}
System.out.println("i = " + i);
```

- What do you think this code does?

Methods and Design-by-Contract (1)

- Design your own methods to perform specific, well-defined tasks
- Each method has a *signature*:

```
public static ReturnType method(paramType1 param1, ... paramTypeN paramN)
{
    // perform certain task
}
```
- Example: a method to compute area of rectangle:

```
public static double findRectArea(double length, double width)
{
    return length * width;
}
```
- Each method has a precondition and a postcondition
 - Precondition: constraints method's caller must satisfy to call method
 - Postcondition: guarantees method provides if preconditions are met
- For our example:
 - Precondition: $\text{length} > 0.0, \text{width} > 0.0$
 - Postcondition: returns $\text{length} \times \text{width}$ (area of rectangle)

Methods and Design-by-Contract (2)

- In practice, methods are annotated via JavaDoc,

e.g.,

```
/**
```

```
    Compute area of rectangle.
```

```
    @param length Length of rectangle
```

```
    @param width Width of rectangle
```

```
    @return Area of rectangle
```

```
*/
```

- Methods called from `main()` (which is static) need to be defined static too
- Some methods may not return anything (void)

Array Data Structure

- Array: fixed-length sequence of variable types; cannot change length at run-time

Examples:

```
final int NUMSTUDENTS = 10;
String[] students; // Declaration
String[] students = new String[NUMSTUDENTS];
    // Declaration and initialization
String[] moreStudents = { "Alice", "Bob", "Rohit", "Wei"};
    // Declaration and explicit initialization
System.out.println(moreStudents.length) // Prints 4
```

- Enhanced for loop: executed for each element in array

Example:

```
for (String student: moreStudents)
{
    System.out.println(student + ", ");
}
```

- Prints “Alice, Bob, Rohit, Wei,” to screen
- Array indices are numbered 0, ..., $N-1$; watch for off-by-one errors! `moreStudents[0]` is “Alice”; `moreStudents[3]` is “Wei”

Two-Dimensional Arrays

- We can have two-dimensional arrays.

Example:

```
final int ROWS = 3; final int COLUMNS = 3;
char[][] ticTacToe = new char[ROWS][COLUMNS]; // declare
for (int i = 0; i < ROWS; i++)
{
    for (int j = 0; j < COLUMNS; j++)
    {
        ticTacToe[i][j] = '_'; // Initialize to 'blank'
    }
}
// Tic-tac-toe logic goes here (with 'X's, 'O's)
```

- ticTacToe.length returns number of rows;
- ticTacToe[0].length returns number of columns
- Higher-dimensional arrays are possible too

Parameterized Data Structures

- We can define data structures in terms of an arbitrary variable type (call it Item).
- `ArrayList<Item>`, a variable-length array that can be modified at run-time. Examples:

```
ArrayList<String> arrStrings = new ArrayList<String>();
ArrayList<Double> arrDoubles = new ArrayList<Double>();
arrStrings.add("Alice"); arrStrings.add("Bob"); arrStrings.add("Rohit");
arrStrings.add("Wei");
String str = arrStrings.get(1); // str becomes "Bob"
arrStrings.set(2, "Raj"); // "Raj" replaces "Rohit"
System.out.println(arrStrings.size()); // prints 4
```
- Notice:
 - Need to call `import java.util.ArrayList;` at beginning of program
 - Off-by-one indexing: cannot call `arrStrings.get(4);`
 - *Auto-boxing*: we cannot create an `ArrayList` of doubles. We need to replace `double` with *wrapper class* `Double`. (Recall the “primitive data types” table)
- Other parameterized data types include `Lists`, `Sets`, `Maps`, `Stacks`, `Queues`, `Trees` (see chapters 14–16 in [1])

Exception Handling (1)

- If we had called `arrStrings.get(4)`, we would have an error condition
 - The JVM throws an `IndexOutOfBoundsException` exception, halts execution

```
1 import java.util.ArrayList;
2
3
4 public class ArrayException
5 {
6
7     /**
8      * @param args
9      */
10    public static void main(String[] args)
11    {
12        // TODO Auto-generated method stub
13        ArrayList<String> arrStrings = new ArrayList<String>();
14        arrStrings.add("Alice");
15        arrStrings.add("Bob");
16        arrStrings.add("Rohit");
17        arrStrings.add("Wei");
18        int size = arrStrings.size();
19        arrStrings.get(size);
20    }
21
22 }
23
```

Exception in thread "main" `java.lang.IndexOutOfBoundsException`: Index: 4, Size: 4
at `java.util.ArrayList.rangeCheck(ArrayList.java:604)`
at `java.util.ArrayList.get(ArrayList.java:382)`
at `ArrayException.main(ArrayException.java:19)`

Exception Handling (2)

- We handle exceptions using the try-catch-finally structure:

```
try
{
    // Code that could trigger an exception
}
catch (IndexOutOfBoundsException e) // Or another Exception
{
    // Code that “responds” to exception, e.g.,
    e.printStackTrace();
}
finally
{
    // Code that executes regardless of whether exception occurs
}
```

- There can be many catch blocks for different Exceptions, but there is only one try block and one (optional) finally block. (See Section 7.4 in [1] for the full “hierarchy” of Exceptions)
- Exceptions always need to be caught and “reported”, especially in Android

Outline

- Getting Started
- Java: The Basics
- **Java: Object–Oriented Programming**
- Android Programming

Objects and Classes (1)

- *Classes* serve as “blueprints” that describe the states and behaviors of *objects*, which are actual “instances” of classes
- For example, a Vehicle class describes a motor vehicle’s blueprint:
 - States: “on/off”, driver in seat, fuel in tank, speed, etc.
 - Behaviors: startup, shutdown, drive “forward”, shift transmission, etc.
- There are many possible Vehicles, e.g., Honda Accord, Mack truck, etc. These are *instances* of the Vehicle blueprint
- Many Vehicle states are specific to each Vehicle object, e.g., on/off, driver in seat, fuel remaining. Other states are specific to the class of Vehicles, not any particular Vehicle (e.g., keeping track of the “last” Vehicle ID # assigned). These correspond to *instance fields* and *static fields* in a class.
- Notice: we can operate a vehicle without knowing its implementation “under the hood”. Similarly, a class makes public *instance methods* by which objects of this class can be manipulated. Other methods apply to the set of all Vehicles (e.g., set min. fuel economy). These correspond to *static methods* in a class

Objects and Classes (2)

```
public class Vehicle
{
    // Instance fields (some omitted for brevity)
    private boolean isOn = false;
    private boolean isDriverInSeat = false;
    private double fuelInTank = 10.0;
    private double speed = 0.0;

    // Static fields
    private static String lastVin = "4A4AP3AU*DE999998";

    // Instance methods (some omitted for brevity)
    public Vehicle() { ... } // Constructor
    public void startUp() { ... }
    public void shutOff() { ... }
    public void getIsDriverInSeat() { ... } // getter, setter methods
    public void setIsDriverInSeat() { ... }
    private void manageMotor() { ... } // More private methods ...


    // Static methods
    public static void setVin(String newVin) { ... }
}
```

Objects and Classes (3)

- How to use the `Vehicle` class:
 - First, create a new object via constructor `Vehicle()`, e.g., `Vehicle myCar = new Vehicle();`
 - Change `Vehicle` states, e.g., `startUp()` or `shutOff()` the `Vehicle`
 - You can imagine other use cases
 - Mark a new `Vehicle`'s ID number (VIN) as “taken” by calling `Vehicle.setVin(...)`
 - Caveat: VINs more complex than this (simple) implementation [7]
- Notes:
 - Aliasing: If we set `Vehicle myTruck = myCar`, both `myCar` and `myTruck` “point” to the same variable. Better to perform “deep copy” of `myCar` and store the copy in `myTruck`
 - `null` reference: refers to no object, cannot invoke methods on `null`
 - Implicit parameter and the `this` reference
- Access control: `public`, `protected`, `private`

Inheritance (1)

- Types of Vehicles: Motorcycle, Car, Truck, etc. Types of Cars: Sedan, Coupe, SUV. Types of Trucks: Pickup, Flatbed.
- Induces inheritance hierarchy
- Subclasses inherit fields/methods from superclasses.
- Subclasses can add new fields/methods, override those of parent classes
- For example, Motorcycle's `driveForward()` method differs from Truck's `driveForward()` method



Inheritance (2)

- Inheritance denoted via `extends` keyword

```
public class Vehicle
{
    ...
    public void driveForward
(double speed)
    {
        // Base class method
    }
}
```

```
public class Motorcycle
extends Vehicle
{
    ...
    public void driveForward
(double speed)
    {
        // Apply power...
    }
}
```

Inheritance (3)

```
public class Truck extends Vehicle
{
    private boolean useAwd = true;
...
    public Truck(boolean useAwd) { this.useAwd = useAwd; }
...
    public void driveForward(double speed)
    {
        if (useAwd)
        {
            // Apply power to all wheels...
        }
        else
        {
            // Apply power to only front/back wheels...
        }
    }
}
```

Polymorphism

- Suppose we create Vehicles and invoke the `driveForward()` method:

```
Vehicle vehicle = new Vehicle();  
Vehicle motorcycle = new Motorcycle();  
Truck truck1 = new Truck(true);  
Vehicle truck2 = new Truck(false);  
// Code here to start vehicles...  
vehicle.driveForward(5.0);  
motorcycle.driveForward(10.0);  
truck1.driveForward(15.0);  
truck2.driveForward(10.0);
```
- For `vehicle`, `Vehicle`'s `driveForward()` method is invoked
- For `motorcycle`, `Motorcycle`'s `driveForward()` method is invoked
- With `truck1` and `truck2`, `Truck`'s `driveForward()` function is invoked (with all-wheel drive for `truck1`, not for `truck2`).
- Dynamic method lookup: Java looks at objects' actual types in determining which method to invoke
- Polymorphism: feature where objects of different subclasses can be treated the same way. All Vehicles `driveForward()` regardless of (sub)class.

The Object Class

- *Every* class in Java is a subclass of Object
- Important methods in Object:
 - toString(): Converts the Object into a String representation
 - equals(): Compares “contents” of Objects to see if they’re the same
 - hashCode(): Hashes the Object to a fixed-length String, useful for data structures like HashMap, HashSet
- If you create your own class, you should override toString() and hashCode()

Interfaces

- Java interfaces abstractly specify methods to be implemented
- Intuition: decouple method definitions from implementations (clean design)
- Interfaces, implementations denoted by `interface`, `implements` keywords
- Example:

```
public interface Driveable
{
    public void driveForward(double speed);
}

public class Vehicle implements Driveable
{
    public void driveForward(double speed) { // implementation }
}

public class Motorcycle extends Vehicle implements Driveable
{
    public void driveForward(double speed) { // implementation }
}
```

The Comparable Interface

- Comparing Objects is important, e.g., sorting in data structures
- The Comparable interface compares two Objects, e.g., a and b:

```
public interface Comparable
{
    int compareTo(Object otherObject);
}
```
- `a.compareTo(b)` returns negative integer if a “comes before” b, 0 if a is the same as b, and a positive integer otherwise
- In your classes, you should implement Comparable to facilitate Object comparison

Object-Oriented Design Principles


- Each class should represent a single concept
 - Don't try to fit all functionality into a single class
 - Consider a class per “noun” in problem description
 - Factor functionality into classes, interfaces, etc. that express the functionality with minimal coupling
- For software projects, start from use cases (how customers will use software: high level)
 - Then identify classes of interest
 - In each class, identify fields and methods
 - Class relationships should be identified: is-a (inheritance), has-a (aggregation), implements interface, etc.
- Packages provide class organization mechanism
 - Examples: `java.lang.*`, `java.util.*`, etc.
 - Critical for organizing large numbers of classes!
 - All classes in a package can “see” each other (scope)

Outline


- Getting Started
- Java: The Basics
- Java: Object–Oriented Programming
- **Android Programming**

Introduction to Android

- Popular mobile device OS: 52% of U.S. smartphone market [8]
- Developed by Open Handset Alliance, led by Google
- Google claims 900,000 Android device activations [9]




Source: [8]



Android Highlights (1)

- Android apps execute on Dalvik VM, a “clean-room” implementation of JVM
 - Dalvik optimized for efficient execution
 - Dalvik: register-based VM, unlike Oracle’s stack-based JVM
 - Java .class bytecode translated to Dalvik EXecutable (DEX) bytecode, which Dalvik interprets



Android Highlights (2)


- Android apps written in Java 5
 - Actually, a Java dialect (Apache Harmony)
 - Everything we've learned still holds
- Apps use four main components:
 - Activity: A “single screen” that's visible to user
 - Service: Long-running background “part” of app (*not* separate process or thread)
 - ContentProvider: Manages app data (usually stored in database) and data access for queries
 - BroadcastReceiver: Component that listens for particular Android system “events”, e.g., “found wireless device”, and responds accordingly

App Manifest

- Every Android app must include an `AndroidManifest.xml` file describing functionality
- The manifest specifies:
 - App's Activities, Services, etc.
 - Permissions requested by app
 - Minimum API required
 - Hardware features required, e.g., camera with autofocus
 - External libraries to which app is linked, e.g., Google Maps library

Activity Lifecycle

- Activity: key building block of Android apps
- Extend Activity class, override onCreate(), onPause(), onResume() methods
- Dalvik VM can stop any Activity without warning, so saving state is important!
- Activities need to be “responsive”, otherwise Android shows user “App Not Responsive” warning:
 - Place lengthy operations in Threads, AsyncTasks




Source: [12]

App Creation Checklist

- If you own an Android device:
 - Ensure drivers are installed
 - Enable developer options on device under *Settings*, specifically *USB Debugging*
 - Android 4.2, 4.3: Go to *Settings*→*About phone*, press *Build number* 7 times to enable developer options
- For Eclipse:
 - Make sure you've enabled LogCat, Devices views. Click a connected device in Devices to see its log
 - Programs should log states via `android.util.Log`'s `Log.d(APP_TAG_STR, "debug")`, where `APP_TAG_STR` is a `final String` tag denoting your app
 - Other commands: `Log.e()` (error); `Log.i()` (info); `Log.w()` (warning); `Log.v()` (verbose) – same parameters

Creating Android App (1)


- Creating Android app project in Eclipse:
 - Go to *File*→*New*→*Other...*, select Android Application Project (Android folder), click Next
 - Enter app, project name
 - Choose package name using “reverse URL” notation, e.g., `edu.osu.myapp`
 - Select APIs for app, then click Next



The screenshot shows the 'New Android Application' dialog box in the Eclipse IDE. The dialog has a title bar with standard window controls and the text 'New Android Application'. Below the title bar, there is a sub-header 'New Android Application' and a red 'x' icon with the text 'Enter an application name (shown in launcher)'. The main area contains several input fields and dropdown menus: 'Application Name' (with a red 'x' icon), 'Project Name' (with a red 'x' icon), and 'Package Name' (with a red 'x' icon). Below these are four dropdown menus: 'Minimum Required SDK' (set to 'API 8: Android 2.2 (Froyo)'), 'Target SDK' (set to 'API 17: Android 4.2 (Jelly Bean)'), 'Compile With' (set to 'API 18: Android 4.3 (Jelly Bean)'), and 'Theme' (set to 'Holo Light with Dark Action Bar'). At the bottom, there is a lightbulb icon with the text 'The application name is shown in the Play Store, as well as in the Manage Application list in Settings.' and a row of buttons: '< Back', 'Next >', 'Cancel', and 'Finish'.


Creating Android App (2)

- Click Next for the next two windows
- You'll see the "Create Activity" window. Select "Blank Activity" and click Next.
- Enter Activity's name and click Finish
- This automatically creates "Hello World" app



Deploying the App

- Two choices for deployment:
 - Real Android device
 - Android virtual device
- Plug in your real device; otherwise, create an Android virtual device
- Emulator is slow. Try Intel accelerated version, or perhaps <http://www.genymotion.com/>
- Run the app: right click project name, select *Run As*→*Android Application*



Underlying Source Code

src/.../MainActivity.java

```
package edu.osu.helloandroid;

import android.os.Bundle;
import android.app.Activity;
import android.view.Menu;

public class MainActivity extends Activity
{
    @Override
    protected void onCreate(Bundle savedInstanceState)
    {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }

    @Override
    public boolean onCreateOptionsMenu(Menu menu)
    {
        // Inflate the menu; this adds items to the action bar if it is present.
        getMenuInflater().inflate(R.menu.main, menu);
        return true;
    }
}
```

Underlying GUI Code

res/layout/activity_main.xml

```
<RelativeLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:paddingBottom="@dimen/activity_vertical_margin"
    android:paddingLeft="@dimen/activity_horizontal_margin"
    android:paddingRight="@dimen/activity_horizontal_margin"
    android:paddingTop="@dimen/activity_vertical_margin"
    tools:context=".MainActivity" >

    <TextView
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="@string/hello_world" />
</RelativeLayout>
```

– RelativeLayouts are quite complicated. See [13] for details

The App Manifest

AndroidManifest.xml


```
<?xml version="1.0" encoding="utf-8"?>
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
    package="edu.osu.helloandroid"
    android:versionCode="1"
    android:versionName="1.0" >

    <uses-sdk
        android:minSdkVersion="8"
        android:targetSdkVersion="17" />

    <application
        android:allowBackup="true"
        android:icon="@drawable/ic_launcher"
        android:label="@string/app_name"
        android:theme="@style/AppTheme" >
        <activity
            android:name="edu.osu.helloandroid.MainActivity"
            android:label="@string/app_name" >
            <intent-filter>
                <action android:name="android.intent.action.MAIN" />
                <category android:name="android.intent.category.LAUNCHER" />
            </intent-filter>
        </activity>
    </application>
</manifest>
```

A More Interesting App

- We'll now examine an app with more features: WiFi Tester (code on class website)
- Press a button, scan for WiFi access points (APs), display them



Underlying Source Code (1)

```
@Override
public void onCreate(Bundle savedInstanceState)
{
    super.onCreate(savedInstanceState);
    setContentView(R.layout.activity_wi_fi);

    // Set up WifiManager.
    mWifiManager = (WifiManager) getSystemService(Context.WIFI_SERVICE);

    // Create listener object for Button. When Button is pressed, scan for
    // APs nearby.
    Button button = (Button) findViewById(R.id.button);
    button.setOnClickListener(new View.OnClickListener()
    {
        public void onClick(View v)
        {
            boolean scanStarted = mWifiManager.startScan();

            // If the scan failed, log it.
            if (!scanStarted) Log.e(TAG, "WiFi scan failed...");
        }
    });

    // Set up IntentFilter for "WiFi scan results available" Intent.
    mIntentFilter = new IntentFilter();
    mIntentFilter.addAction(WifiManager.SCAN_RESULTS_AVAILABLE_ACTION);
}
```

Underlying Source Code (2)

- Code much more complex
- First get system `WifiManager`
- Create listener `Object` for button that performs scans
- We register Broadcast Receiver, `mReceiver`, to listen for `WifiManager`'s "finished scan" system event (expressed as `Intent` `WifiManager.SCAN_RESULTS_AVAILABLE_ACTION`)
- Unregister Broadcast Receiver when leaving `Activity`

```
@Override
protected void onResume()
{
    super.onResume();
    registerReceiver(mReceiver,
mIntentFilter);
}
```

```
@Override
protected void onPause()
{
    super.onPause();
    unregisterReceiver(mReceiver);
}
```

The Broadcast Receiver

```
private final BroadcastReceiver mReceiver = new BroadcastReceiver()
{
    @Override
    public void onReceive(Context context, Intent intent)
    {
        String action = intent.getAction();
        if (WifiManager.SCAN_RESULTS_AVAILABLE_ACTION.equals(action))
        {
            Log.e(TAG, "Scan results available");
            List<ScanResult> scanResults = mWifiManager.getScanResults();
            mApStr = "";
            for (ScanResult result : scanResults)
            {
                mApStr = mApStr + result.SSID + "; ";
                mApStr = mApStr + result.BSSID + "; ";
                mApStr = mApStr + result.capabilities + "; ";
                mApStr = mApStr + result.frequency + " MHz;";
                mApStr = mApStr + result.level + " dBm\n\n";
            }
            // Update UI to show all this information.
            setTextView(mApStr);
        }
    }
};
```

User Interface

Updating UI in code

```
private void setTextView(String str)
{
    TextView tv = (TextView)
findViewById(R.id.textview);
    tv.setMovementMethod(new
ScrollingMovementMethod());
    tv.setText(str);
}
```

- This code simply has the UI display all collected WiFi APs, makes the text information scrollable

UI Layout (XML)

```
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="fill_parent"
    android:layout_height="fill_parent"
    android:orientation="vertical">

    <Button
        android:layout_width="fill_parent"
        android:layout_height="wrap_content"
        android:id="@+id/button"
        android:text="@string/button_text"/>

    <TextView
        android:id="@+id/header"
        android:layout_width="fill_parent"
        android:layout_height="wrap_content"
        android:text="@string/ap_list"
        tools:context=".WifiActivity"
        android:textStyle="bold"
        android:gravity="center">
    </TextView>

    <TextView
        android:layout_width="fill_parent"
        android:layout_height="fill_parent"
        tools:context=".WifiActivity"
        android:id="@+id/textview"
        android:scrollbars="vertical">
    </TextView>
</LinearLayout>
```

Android Programming Notes

- Android apps have multiple points of entry: no `main()` method
 - Cannot “sleep” in Android
 - During each entrance, certain Objects may be `null`
 - Defensive programming is very useful to avoid crashes, e.g.,
`if (!(myObj == null)) { // do something }`
- Java concurrency techniques are required
 - Don’t block the “main” thread in Activities
 - Implement long-running tasks such as network connections asynchronously, e.g., as `AsyncTasks`
 - Recommendation: read [4]; chapter 20 [10]; [11]
- Logging state via `android.util.Log` throughout app is essential when debugging (finding root causes)
- Better to have “too many” permissions than too few
 - Otherwise, app crashes due to security exceptions!
 - Remove “unnecessary” permissions before releasing app to public
- Event handling in Android GUIs entails many listener Objects

Concurrency: Threads (1)

- Thread: program unit (within process) executing independently
- Basic idea: create class that implements Runnable interface
 - Runnable has one method, run(), that contains code to be executed
 - Example:

```
public class OurRunnable implements Runnable
{
    public void run()
    {
        // run code
    }
}
```
- Create a Thread object from Runnable and start() Thread, e.g.,

```
Runnable r = new OurRunnable();
Thread t = new Thread(r);
t.start();
```
- Problem: this is cumbersome unless Thread code is reused

Concurrency: Threads (2)

- Easier approach: anonymous inner classes, e.g.,

```
Thread t = new Thread(new Runnable()
{
    public void run()
    {
        // code to run
    }
});
t.start();
```
- Idiom essential for one-time network connections in Activities
- However, Threads can be difficult to synchronize, especially with UI thread in Activity. AsyncTasks are better suited for this

Concurrency: AsyncTask

- AsyncTask encapsulates asynchronous task that interacts with UI thread in Activity:

```
public class AsyncTask<Params, Progress, Result>
{
    protected Result doInBackground(ParamType param)
    {
        // code to run in background
        publishProgress(ProgressType progress); // UI
        ...
        return Result;
    }

    protected void onProgressUpdate(ProgressType progress)
    {
        // invoke method in Activity to update UI
    }
}
```

- Extend AsyncTask with your own class
- Documentation at <http://developer.android.com>

Thank You

Any questions?

References (1)

1. C. Horstmann, *Big Java Late Objects*, Wiley, 2012. Online: <http://proquest.safaribooksonline.com.proxy.lib.ohio-state.edu/book/-/9781118087886>
2. J. Bloch, *Effective Java*, 2nd ed., Addison–Wesley, 2008. Online: <http://proquest.safaribooksonline.com.proxy.lib.ohio-state.edu/book/programming/java/9780137150021>
3. S.B. Zakhour, S. Kannan, and R. Gallardo, *The Java® Tutorial: A Short Course on the Basics*, 5th ed., Addison–Wesley, 2013. Online: <http://proquest.safaribooksonline.com.proxy.lib.ohio-state.edu/book/programming/java/9780132761987>
4. C. Collins, M. Galpin, and M. Kaeppler, *Android in Practice*, Manning, 2011. Online: <http://proquest.safaribooksonline.com.proxy.lib.ohio-state.edu/book/programming/android/9781935182924>
5. M.L. Sichitiu, 2011, <http://www.ece.ncsu.edu/wireless/MadeInWALAN/AndroidTutorial/PPTs/javaReview.ppt>
6. Oracle, <http://docs.oracle.com/javase/1.5.0/docs/api/index.html>
7. Wikipedia, https://en.wikipedia.org/wiki/Vehicle_Identification_Number
8. Nielsen Co., “Who’s Winning the U.S. Smartphone Market?”, 6 Aug. 2013, <http://www.nielsen.com/us/en/newswire/2013/whos-winning-the-u-s-smartphone-market-.html>
9. Android Open Source Project, <http://www.android.com>

References (2)

10. <http://bcs.wiley.com/he-bcs/Books?action=index&itemId=1118087887&bcsId=7006>
11. B. Goetz, T. Peierls, J. Bloch, J. Bowbeer, D. Holmes, and D. Lea, Java Concurrency in Practice, Addison-Wesley, 2006, online at <http://proquest.safaribooksonline.com/book/programming/java/0321349601>
12. <https://developer.android.com/guide/components/activities.html>
13. <https://developer.android.com/guide/topics/ui/declaring-layout.html#CommonLayouts>